(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Betex Melamine 185

Document No.: TDS-SB0020Rev01 Revised Date: 1/Nov/2016

Description	A two-pack alkyd-melamine based acid curing finish					
Decemmended Hee						
Recommended Use	Finishing coat for parquet flooring					
Characteristics	Fast Drying					
	Good chemical resistance					
	Good scratch resistance					
	Good durability					
Finish	Gloss/ Satin/ Matt					
	Close, Califf Mal					
Technical Data	Mixing Ratio	:	Base :		AC Hardener	
		=			<u> </u>	
	Pot Life (30°C)	:	6 - 8 hou Thinner)	our	(after dilution with Brightex	
	Specific Gravity (25°C)	:	0.99 ± 0.02	2		
	Flash Point	:	25°C			
A 1' (' D (A 1' (' M () 1		0 0			
Application Data	Application Method Thinner		Spray or Brush Brightex Thinner 10 – 30% by volume Approx. 10 m²/L Approx. 20 microns			
	Dilution					
	Theoretical Coverage	•				
	Dry Film Thickness					
	Drying Time (30°C)	:			: Approx. 10 – 15 minutes	
			Hard Dry		: Approx. 24 hours	
Divertions of Use	Make aure the negrount fla		امام محمل مام			
Directions of Use	Make sure the parquet floor is dry and clean Sand to ensure a smoot surface and to remove foreign matters befo					
	coating.					
	Apply 1 – 2 coat(s) of Bet	tex	x Melamine Clear 185.			
Packaging	4.5 L					
Storage	Should be tightly sealed and stored in cool, dry place.					
Otorage	Keep away from open flames.					
	7 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
Handling and Safety	As it contains solvent, the product requires special care in handling.					
	Avoid any eye and skin contact. For further information please refer to SDS.					



(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Disclaimer

Betex Melamine 185

Document No.: TDS-SB0020Rev01 Revised Date: 1/Nov/2016

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from
time to time, and without notice, in light of our experience and product
development.